



PowerBrick Smart

Lithium-Ion battery

12V-70Ah-AB-BT

12V battery pack - Lithium Iron-Phosphate (LiFePO₄) - 70Ah

- Ultra safe **Lithium Iron Phosphate** chemistry (no thermal run-away, no fire or explosion risks)
- **Embedded BMS** (Battery Management System)
- **High performance active cell balancing (up to 1A current)**
- **Bluetooth monitoring (SOC, cell voltage, SOH, etc.)**
- No **Lead**, no **rare earths**, no **acid**, no **degassing**
- **High Service Life : 3000 cycles** and more (see chart)
- Calendar life > **10 years**
- Excellent **temperature** robustness (-20 °C up to +60 °C)
- **Flexible deployment** : up to **16 packs in parallel** and **4 in series**
- **Constant power** during discharge (very low internal resistance)
- **Partial or deep discharge** allowed up to 100 %
- **Very low Peukert's losses** (energy efficiency >98 %)
- **Very low self discharge** (<3 % per month)
- **No memory effect**
- About **50 % lighter** and **40% smaller** than equivalent Lead-AGM battery with same usable energy
- **Certification :CE, RoHS, UN 38.3**

Technical Specifications


Electric	Nominal voltage / Nominal capacity	12.8V / 70Ah
	Stored energy	896 Wh
	Volumetric energy density / Specific energy	135.8 Wh/L / 110.6 Wh/Kg
	Internal resistance	≤ 40mΩ
	Cycles	>3000 cycles (see chart)
	Self discharge	< 3% per month
	Energy efficiency	> 98%
Standard Charge	Charge voltage	14.4 V ± 0.2 V (Optional floating voltage : 13.36V max)
	Charge mode	CC/CV : Constant Current / Constant Voltage
	Continuous charge current / Maximum charge current	35 A / 70A
	BMS charge cut-off voltage	14.8 V ± 0.1V
Standard Discharge	Instant peak discharge current	250 A ± 30 A (max 100mS)
	Continuous discharge current	100 A (1.28 kW)
	Maximum discharge current (< 30s)	150 A (1.92 kW)
	BMS discharge cut-off voltage	10 V
Environment	Charge temperature range	0°C to +60°C
	Discharge temperature range	-20°C to +60°C
	Storage temperature	0°C to +50°C @60±25% relative humidity
	IP protection level	IP 65
Mechanical	Type of cells	Cylindrical
	Casing material	ABS
	Dimensions	L : 228mm x W : 138mm x H : 210 mm
	Weight	8.1 kg
	Terminal	M8 bolt



APPLICATIONS

- **Electrical vehicules and utilities**
- **Solar and wind energy storage**
- **Marine**
- **Street lightning**
- **CCTV and security camera**
- **UPS, electric back-up**
- **Telecom**
- **Medical equipments**

...









PowerBrick Smart




Lithium-Ion battery

12V-70Ah-AB-BT

Charts and curves



Dimensions



V1.5

PowerTech Systems SAS
ZA Charles Renard - Batiment A1
6 Bld Georges Guynemer
78210 ST CYR L'ECOLE - France

SAS au capital de 1 000 000 Euros
SIREN : 793926577 - TVA : FR33793926577

www.powertechsystems.eu
+33 185 400 970
contact@powertechsystems.eu